



DECLARATION OF PERFORMANCE

No.: 002-2

METEON®

Unique identification code of the product-type		METEON®
Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer		Compact laminate panels for external wall and ceiling finishes Type EDS according to EN438 part 6
Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)		TRESPA International B.V. Wetering 20 / NL – 6002 SM Weert
System or systems of AVCP (=assessment and verification of constancy of performance)		System 3
Name and identification number of the notified body		NB 1173 / WFRGENT N.V.
Declared performance		
Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	D-s2,d0	EN 438 – 7:2005
Fire Resistance	NPD	
Water vapour permeability	NPD	
Resistance to fixings	6 mm ≥ 2.000 N 8 mm ≥ 3.000 N ≥ 10 mm ≥ 4.000 N	
Direct airborne sound insulation	NPD	
Flexural tensile strength	≥ 120 MPa	
Flexural modulus of elasticity	≥ 9000 MPa	
Thermal resistance / conductivity	NPD	
Thermal shock resistance: Climatic shock	Appearance ≥ 4 Ds ≥ 0.95 / Dm ≥ 0.95	
Durability: Resistance to wet conditions	Appearance ≥ 4 Mass Increase ≤ 3 %	
Durability: Density	≥ 1,35 g/cm ³	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

J.A.L. Horbach (CEO)

Weert, The Netherlands, November 1st, 2015